



Plate-Link Steel Belt – Pitch 50mm The Plate-Link Steel Belt is being used in freezing tunnels and for industry where strength is needed. To make the belt even stronger the belt is also made with reinforcement links, side chains and even center chains. The plate thickness is 1,5mm and the rod size is Ø7,0mm.

Standard material: SS304 or SS316

- Side chains** See page 16-17
- Flights** See page 14-15
- Side guards** See page 14-15
- Belt width** The belt can be made in any width up to 6000mm
- Sprockets** See page 18-19



Plate-Link Belt

With closed top




Plate-Link Belt

With perforated top




Plate-Link Belt


With closed top & polished non-stick surface

HEAVY Plate-Link - Pitch 50mm The Heavy Plate-Link belt is for high load applications where strength and reliability is the key word. Delivered with closed surface or with perforation, hole sizes are available upon request. Heavy Plate-Link in 2,5mm stainless steel plate SS304 or SS316. Rod size: Ø12mm! The belt requires side chain for its drive.

Standard material: SS304 or SS316

Rod size: Ø12mm

- Flights** See page 14-15
- Side guards** See page 14-15
- Sprockets** See page 18-19



Heavy Plate-Link

With closed top



Heavy Plate-Link

With perforated top



Plate-Link Belts Heavy Plate-Link Belts

